



ISUZU CITIPOINT 18

Manufactured by Anadolu Isuzu
The one and only "Isuzu Manufacturing Management (IMM)" certified Isuzu factory in Europe.

ISUZU CITIPORT 18

TECHNICAL SPECIFICATIONS

Dimensions (mm)

Maximum Length	18200
Maximum Width	2550
Maximum Height	3136
Wheelbase 1,2	5850, 6170
Front Overhang	2700
Rear Overhang	3480

Weights (kg)

Gross Vehicle Weight	29000
----------------------	-------

Engine

Model	Cummins L9E6E370B
Type	Commonrail Turbo Diesel Intercooler
Number of Cylinders	6
Displacement (cc)	8900
Maximum Power (kw(PS)/rpm)	269 (365) / 2100
Maximum Torque (Nm/rpm)	1584 / 1300
Emission Standard	Euro VI OBD-E

Transmission

Model	ZF 6AP 1700B, Automatic
Number of Gears	6 Forward, 1 Reverse

Steering System

Hydraulic and Adjustable Dashboard and Steering
Wheel Column in Height and Inclination

Tyres

Tyre Sizes	275/70 R22,5
------------	--------------

Suspension

Front	Independent Air Suspansion, 2 Air Bellows, 2 Hydraulic Shock Absorbers
Middle	4 Air Bellows, 4 Hydraulic Shock Absorbers
Rear	4 Air Bellows, 4 Hydraulic Shock Absorbers
Anti Roll Bar	S
Kneeling System (ECAS & ELC)	S

Brake System

Front / Middle / Rear	Disc / Disc / Disc
System	Full Air Brake System With ABS (EBS) and ASR (EBS) , Dual Circuit, Auto-Adjusted Water Sperator System is Optional Air Actuated, Operating on Middle and Rear Axle Intarder
Parking Brake	
Auxiliary Brake	

Fuel Tank


Fuel Tank Capacity (lt)	300
Adblue Tank (lt)	43

Electrical System

Battery	24V (2x12V) - 240 Ah
---------	----------------------

Passenger Capacity

Maximum Passenger Capacity	155
Standard Layout	46 Seated + 109 Standing
Layout with Wheelchair	40 Seated + 2 Wheelchair + 107 Standing



EQUIPMENTS

Heating and Ventilation

Pre Heater	Opt
------------	-----

Air Conditioner

Digital Air Conditioner	S
A/C Dashboard Nozzle Diffuser for Driver	S
A/C With Heater	Opt

Safety & Driving Comfort

Speed Limitor	S
Tachograph	S
Multiplex System	S
ABS	S
ASR	S
EBS	S
EBD	S
Bus Stop Brake (BSB)	S
Hillholder	S
Retarder	S
Parking Sensor	S
Spare Wheel	S
Tyre Inflation Set	S
Roof Hatch for Ventilation & Emergency Exit	S (3 Units with Electrical Control)
Reverse Gear Warning Beeper	S
Fire Extinguisher	S
Engine Compartment Fire Detection and Automatic Fire Supression System	S
Fog Lamps	S (Front / Rear)
Day Time Running Lamps (DRL)	S
Locking System	S
Battery Main Switch	S

Exterior

Metallic Paint	Opt
Side Stripe Stickers	Opt
Towing Device	S

Doors

Number of Service Doors	4 Doors (S), 3 Doors (Opt)
Type of Service Doors	Double Wings, Pneumatic, Inward Swing
Wheelchair Ramp	Manual with Sensor
Remote Control	S (Front Service Door)

Passenger Windows

Type	1/4 Hinged Passenger Windows (S), Sliding Passenger Window (Opt) Single Glazed (S), Double Glazed (Opt)
------	---

Layers of Glass

Driver Windows

Windshield	Single Piece Laminated
Driver's Window	With Resistance Heater, Electrically Controlled
Front Door Window	Double Glazed (S)

Interior

Driver Seat

Windshield Blind	S (Electrically Controlled Roller Blind For Windscreen)
Driver Curtain	S (Manual)
Driver's Seat	Air Actuated, Adjustable
Electrically Controlled Side Mirrors	S
Heated Side Mirrors	S
Driver's Cabin	Semi Glass (S), Full Glass (Opt)
Driver Overhead Cabinet	S (Locker)
Coathanger for The Driver	S
Ticket Validator Preparation	Opt
Lamp for Driver Seat	S
USB Charger for Driver	S

Passenger Compartment

Passenger Seat Material	Cloth Ped On Plastic
USB Charger for Passangers	S

Lightening & Signalization

Interior Ceiling Lighting	S (Continuous type with LED)
Stop Buttons & Signboard	S
Digital Destination Display	Front, Rear (S), Colored (Opt)

Audio & Visual

Camera Systems	S
Camera Monitor on Dashboard	S
Recording Device (DVR)	S
Radio System	S
Monitor / LCD Screen (Passenger Compartment)	S
Digital Clock	S
Wifi Preparation	S
Driver Speaker	S
Announcement System for Passenger Area	Opt

ANADOLU ISUZU

S: Standard Opt: Optional

* Different seating variations are available.